



Self-propelled aerial work platforms

Three air intakes in bucket

Electrical controls in the bucket to press with feet

Working height:
10 m, 11 m y 12 m

Towable



www.mecaplus.es



Features

- ✓ Self-propelled and may be towed
- ✓ Inclination alarm
- ✓ Oil and temperature sound alarm
- ✓ Electrical controls in the bucket to press with feet
- ✓ Hydrostatic transmission with geared motors
- ✓ Independent hydraulic circuits
- ✓ Possibility to perform up to five movements simultaneously
- ✓ Large capacity diesel oil tank (60 hours of work)
- ✓ Object holder box of 100 l
- ✓ All of the pipes inside the arms
- ✓ Built out of 3 mm steel plate to withstand falling objects
- ✓ Electric accelerator
- ✓ Hydraulic pistons with parachute system, flow regulator and non-return valve
- ✓ Emergency lowering device in the bucket and at the base
- ✓ Object holder tray in the bucket
- ✓ Three air intakes in bucket
- ✓ Pneumatic equipment of 820 l/m
- ✓ Maximum weight: 3000 kg. Easy to transport
- ✓ Diesel engine cooled by water or by air
- ✓ Working height: 10 m, 11 m y 12 m
- ✓ Maximum width of transport: 2,10 m
- ✓ Maximum length of transport : 6,75 m



Specifications	MTP-10	MTP-11	MTP-12
Maximum working height	10 m	11 m	12 m
Maximum horizontal reach	4 m	5 m	4,5 m
Distance to earth with max. reach	3,5 m	3,5 m	4,5 m
Maximum weight allowed in bucket	120 kg	120 kg	120 kg
Size of the platform	0,6 m x 0,6 m		
Width A	2,10 m	2,10 m	2,10 m
Height when lowered B	2,07 m	2,07 m	2,42 m
Length when lowered C	5,75 m	6,75 m	6,70 m
Maximum weight	3000 kg	3000 kg	3000 kg
Max. slope of cross axis	32%	32%	32%
Max. slope of longitudinal axis	15%	15%	15%
Hydraulic tank	50 l	50 l	50 l
Diesel oil tank	80 l	80 l	80 l
Engine	Diesel cooled by water or by air		

Options

- ▶ 4x4
- ▶ Rubber tracks
- ▶ Twin wheels

Safety

- ▶ EC type exam certificate machinery directive (EN 280)
- ▶ Automatic levelling system
- ▶ Battery switch
- ▶ Emergency stop
- ▶ Emergency manual lowering

